



MOBILE

# LNx3 3-Inch Mobile Printer

Durable, rugged direct thermal printer with intuitive set-up and interface for premium printing performance for transportation and logistics, retail, and manufacturing applications.

## Overview



LNx3 mobile label and receipt printer brings the power and reliability of Honeywell printers into a durable, lightweight, direct thermal printer meeting or exceeding industry printer specifications.

The large 2.4 inch color screen display streamlines configuration and operation at the touch of a button and is backed up by a fast energy-saving processor and powerful printheads and high-performance motors.

With leading print speeds up to 5ips, the LNx3 printer supports large-volume label and receipt printing requirements in longer intervals helping boost productivity. A removable high-capacity battery and precise power management system provides uninterrupted printing across long operating and standby times.

Effortlessly connect with MFi, NFC pairing, and both Bluetooth® and Wi-Fi options. Print from almost any device with Windows®, iOS, and Android™ compatibility.

Drive productivity and improve inventory management with the LNx3 Mobile Printer.

## Specifications

### FEATURES

**Compatible Drivers**

- Driver for Linux
- Windows

# DIMENSIONS

---

**Overall Dimensions**

- H x W x D: 117 mm x 137 mm x 55 mm (4.53 in x 5.31 in x 2.05 in)

# SOFTWARE & FIRMWARE

---

**2D Barcodes**

- All major 2D barcodes

**Linear Barcodes**

- All major 1D barcodes

**Downloadable Font Type**

- Bitmap Font
- TrueType Font

**Printer Command Language**

- CPCL
- ESC/P
- ESC/POS
- XSIM
- ZPL

**Image File Format**

- BMP
- Bitmap

# PRINTING SPECIFICATIONS

---

**Print Speeds**

- 25-125 mm/s (1-5 ips)

**Resolutions**

- 203 dpi

**Print Method**

- Direct Thermal

# MEDIA

---

**Printer Media Type**

- Label
- Receipt

**Maximum Media Roll Diameter**

- 43 mm (1.69 in)

# HARDWARE

---

**Printer Connection Interface**

- USB C

## ELECTRICAL

---

**Battery Capacity Options**

- 2800 mAh

**Operating voltage**

- 100 to 240 VAC

## ENVIRONMENTAL

---

**Operating Humidity**

- 10% - 90 % non-condensing

## STANDARDS & APPROVALS

---

**Protection Ratings**

- IP54

**Drop Specifications**

- 1.8 m (6 ft)

**Tumble Specifications**

- 1,000 cycles at 0.5 m (1.6 ft) with carrying bag

## NETWORK

---

**Bluetooth Specifications**

- Bluetooth 5.0 + BLE

## OTHERS

---

**Features**

- Rugged and reliable

**Application**

- Healthcare
- Manufacturing
- Retail
- T&L

**Wireless Communication**

- IEEE 802.11 a/b/g/n
- NFC for pairing

**Storage Temperature**

- -20°C to +70°C (-4°F to +158°F)

**Operating temperature**

- -15°C to 55°C (5°F to 131°F)

Warranty Duration

- One year factory warranty

Platform

- Others

**Honeywell**  
Industrial Automation  
855 S Mint St  
Charlotte, NC 28202  
800-582-4263

**LNx3 3-Inch Mobile Printer**  
© 2024 Honeywell International Inc.  
All rights reserved.



This document was generated on 2024-06-06 14:50:44 (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.